

Arizona 1300 series

# READY WHEN YOU ARE

Canon

Canon

---

# TECHNICAL SPECIFICATIONS

## ARIZONA 13x0 GT

Specification	Description																																																																																																															
Printing technology	4/6/8-channel piezoelectric inkjet system using VariaDot imaging technology; with one 636-nozzle, variable droplet printhead per channel.																																																																																																															
Ink configurations	1340 GT: CMYK   1360 GT: CMYK+WW/V   1380 GT: CMYK+WW/V +cm																																																																																																															
Resolution	Variable droplet sizes from 6 to 42 picolitres. The ability to vary the drop size to 6 picolitres produces sharp images with smoother gradients and quartertones. The ability to jet larger droplets up to 42 picolitres produces uniform colours. The result is near-photographic quality with sharpness only before seen at resolutions of 1,440 dpi or higher. Text as small as 2 pt. is perfectly legible (with High Definition mode).																																																																																																															
Print speed	<table border="1"> <thead> <tr> <th rowspan="2">Print Modes</th> <th colspan="3">Arizona 13x0 GT</th> <th colspan="2">Flatbed</th> <th colspan="2">RMO</th> </tr> <tr> <th>1340 GT</th> <th>1360 GT</th> <th>1380 GT</th> <th>m<sup>2</sup>/h</th> <th>ft<sup>2</sup>/h</th> <th>m<sup>2</sup>/h</th> <th>ft<sup>2</sup>/h</th> </tr> </thead> <tbody> <tr> <td>High-Key</td> <td>•</td> <td>•</td> <td>•</td> <td>50.9</td> <td>547.9</td> <td>38.6</td> <td>415.5</td> </tr> <tr> <td>Express</td> <td>•</td> <td>•</td> <td>•</td> <td>34.2</td> <td>368.1</td> <td>25.8</td> <td>277.7</td> </tr> <tr> <td>Production-Fast</td> <td></td> <td></td> <td>•</td> <td>25.2</td> <td>271.3</td> <td>18.8</td> <td>202.4</td> </tr> <tr> <td>Production</td> <td>•</td> <td>•</td> <td>•</td> <td>20.8</td> <td>223.9</td> <td>17</td> <td>183.0</td> </tr> <tr> <td>Quality</td> <td>•</td> <td>•</td> <td>•</td> <td>14.6</td> <td>157.2</td> <td>12</td> <td>129.2</td> </tr> <tr> <td>Quality-Matte</td> <td>•</td> <td>•</td> <td>•</td> <td>10.4</td> <td>111.9</td> <td>7.9</td> <td>85.0</td> </tr> <tr> <td>Quality-Density</td> <td>•</td> <td>•</td> <td>•</td> <td>7.9</td> <td>85.0</td> <td>6.3</td> <td>67.8</td> </tr> <tr> <td>Quality-Layered (2)</td> <td></td> <td>•</td> <td>•</td> <td>7.3</td> <td>78.6</td> <td>6</td> <td>64.6</td> </tr> <tr> <td>Quality-Layered (3)</td> <td></td> <td>•</td> <td>•</td> <td>4.8</td> <td>51.7</td> <td>4</td> <td>43.1</td> </tr> <tr> <td>Fine Art</td> <td>•</td> <td>•</td> <td>•</td> <td>11.7</td> <td>125.9</td> <td>9.5</td> <td>102.3</td> </tr> <tr> <td>High Definition</td> <td>•</td> <td>•</td> <td>•</td> <td>6.2</td> <td>66.7</td> <td>6</td> <td>64.6</td> </tr> <tr> <td>Varnish (High Gloss)</td> <td></td> <td>•</td> <td>•</td> <td>~4</td> <td>43.1</td> <td>n.a.</td> <td>n.a</td> </tr> </tbody> </table>	Print Modes	Arizona 13x0 GT			Flatbed		RMO		1340 GT	1360 GT	1380 GT	m <sup>2</sup> /h	ft <sup>2</sup> /h	m <sup>2</sup> /h	ft <sup>2</sup> /h	High-Key	•	•	•	50.9	547.9	38.6	415.5	Express	•	•	•	34.2	368.1	25.8	277.7	Production-Fast			•	25.2	271.3	18.8	202.4	Production	•	•	•	20.8	223.9	17	183.0	Quality	•	•	•	14.6	157.2	12	129.2	Quality-Matte	•	•	•	10.4	111.9	7.9	85.0	Quality-Density	•	•	•	7.9	85.0	6.3	67.8	Quality-Layered (2)		•	•	7.3	78.6	6	64.6	Quality-Layered (3)		•	•	4.8	51.7	4	43.1	Fine Art	•	•	•	11.7	125.9	9.5	102.3	High Definition	•	•	•	6.2	66.7	6	64.6	Varnish (High Gloss)		•	•	~4	43.1	n.a.	n.a
Print Modes	Arizona 13x0 GT			Flatbed		RMO																																																																																																										
	1340 GT	1360 GT	1380 GT	m <sup>2</sup> /h	ft <sup>2</sup> /h	m <sup>2</sup> /h	ft <sup>2</sup> /h																																																																																																									
High-Key	•	•	•	50.9	547.9	38.6	415.5																																																																																																									
Express	•	•	•	34.2	368.1	25.8	277.7																																																																																																									
Production-Fast			•	25.2	271.3	18.8	202.4																																																																																																									
Production	•	•	•	20.8	223.9	17	183.0																																																																																																									
Quality	•	•	•	14.6	157.2	12	129.2																																																																																																									
Quality-Matte	•	•	•	10.4	111.9	7.9	85.0																																																																																																									
Quality-Density	•	•	•	7.9	85.0	6.3	67.8																																																																																																									
Quality-Layered (2)		•	•	7.3	78.6	6	64.6																																																																																																									
Quality-Layered (3)		•	•	4.8	51.7	4	43.1																																																																																																									
Fine Art	•	•	•	11.7	125.9	9.5	102.3																																																																																																									
High Definition	•	•	•	6.2	66.7	6	64.6																																																																																																									
Varnish (High Gloss)		•	•	~4	43.1	n.a.	n.a																																																																																																									
Ink system	IJC357 UV-curable inks packed in quick-change, 2 litre bags for: Black, Cyan, Magenta, Yellow, Light Cyan, Light Magenta. White and Varnish packed in 1 litre bags.																																																																																																															
System architecture	True flatbed for rigid media printing with available Roll Media Option for flexible media printing.																																																																																																															
Geometric accuracy	<table border="1"> <thead> <tr> <th rowspan="2"></th> <th colspan="2">Measured Over (mm)</th> <th colspan="2">Maximum Error (mm)</th> </tr> <tr> <th>Flatbed</th> <th>RMO</th> <th>Flatbed</th> <th>RMO</th> </tr> </thead> <tbody> <tr> <td>Line length (system width)</td> <td>2,500</td> <td>2,190</td> <td>± 0.8</td> <td>± 0.6</td> </tr> <tr> <td>Line length (system height)</td> <td>1,250</td> <td>2,000</td> <td>± 0.4</td> <td>± 1.5</td> </tr> <tr> <td>Line straightness (system width)</td> <td>2,500</td> <td>2,190</td> <td>0.7</td> <td>0.7</td> </tr> <tr> <td>Line straightness (system height)</td> <td>1,250</td> <td>2,000</td> <td>0.5</td> <td>2.0</td> </tr> <tr> <td>Diagonal Error ("square-ness")</td> <td>1,250x2,500</td> <td>2,000x2,190</td> <td>1.0</td> <td>2.5</td> </tr> </tbody> </table>		Measured Over (mm)		Maximum Error (mm)		Flatbed	RMO	Flatbed	RMO	Line length (system width)	2,500	2,190	± 0.8	± 0.6	Line length (system height)	1,250	2,000	± 0.4	± 1.5	Line straightness (system width)	2,500	2,190	0.7	0.7	Line straightness (system height)	1,250	2,000	0.5	2.0	Diagonal Error ("square-ness")	1,250x2,500	2,000x2,190	1.0	2.5																																																																													
	Measured Over (mm)		Maximum Error (mm)																																																																																																													
	Flatbed	RMO	Flatbed	RMO																																																																																																												
Line length (system width)	2,500	2,190	± 0.8	± 0.6																																																																																																												
Line length (system height)	1,250	2,000	± 0.4	± 1.5																																																																																																												
Line straightness (system width)	2,500	2,190	0.7	0.7																																																																																																												
Line straightness (system height)	1,250	2,000	0.5	2.0																																																																																																												
Diagonal Error ("square-ness")	1,250x2,500	2,000x2,190	1.0	2.5																																																																																																												
Rigid media	Maximum Area: 125 x 250 cm / 49.2 x 98.4 inches Maximum Thickness: 50.8 mm / 2.0 inches Maximum Mass: 34 kg/m <sup>2</sup> / 7 lbs/ft <sup>2</sup>																																																																																																															
Rigid media print area	Up to: 126 x 251 cm / 49.6 x 98.8 inches (for edge-to-edge printing)																																																																																																															
Media roll specification	90 to 220 cm / 35.4 to 86.6 inches. Up to 50 kg / 110 lbs (at any width). Maximum diameter: 240 mm (9.45 inches). Core: 3 inches (inside). Bias: Print-side-in or print-side-out. Most types (application dependent)																																																																																																															
Roll media print width	Up to 219 cm / 86.2 inches																																																																																																															
Image processing	ONYX Thrive 18 (421 configuration or greater recommended)																																																																																																															
Connectivity	10/100/1000 Base-T																																																																																																															
Arizona Xpert	Arizona Xpert offers a unique tool set to save time and money in the creation of complex, multi-layered and duplex applications. The "Arizona Xpert Resale license" and the "Add Arizona Xpert Permission" are included with every Arizona 1300 printer and require ONYX Thrive to be installed.																																																																																																															
Electrical power / Compressed air	2 x 200-240 VAC, 50/60 Hz, Single-phase, 16A per circuit Circuit Breakers: North America: 20A. Europe: 16A. ROW: See CB Scheme Report Clean, dry, compressed air using a Coalescing Filter. Pressure Regulator set to 690 kPa (100 psi) and connects air regulator to 0.5 inch or 12mm OD air tubing. Peak flow: 57 l/min at 690 kPa (2 cfm at 100 psi)																																																																																																															
Environment	Temperature: 18° to 30° C (64° to 86° F) Relative humidity: 30 to 70% (non-condensing) Ventilation: 1,200 m <sup>3</sup> per hour / 700 cfm minimum (see Site Preparation Guide) Altitude: 2,750 m (9,020 feet) maximum, however some components specify a limit of 2,000 m (6,560 feet)																																																																																																															
Size/Weight	Printer only: 4.66 m x 2.0 m (183.5" x 78.7"), 849 kg (1,871 lbs.) Printer + Roll Media Option: 4.66 m x 2.29 m (183.5" x 90.2"), 1,099 kg (2,423 lbs.) Table height: 0.88 m (34.6") / Overall height: 1.3 m (51.2")																																																																																																															

# ARIZONA 13x0 XT

Specification	Description																																																																																																															
<b>Printing technology</b>	4/6/8-channel piezoelectric inkjet system using VariaDot imaging technology; with one 636-nozzle, variable droplet printhead per channel.																																																																																																															
<b>Ink configurations</b>	1340 XT: CMYK   1360 XT: CMYK+WW/V   1380 XT: CMYK+WW/V +cm																																																																																																															
<b>Resolution</b>	Variable droplet sizes from 6 to 42 picolitres. The ability to vary the drop size to 6 picolitres produces sharp images with smoother gradients and quartertones. The ability to jet larger droplets up to 42 picolitres produces uniform colours. The result is near-photographic quality with sharpness only before seen at resolutions of 1,440 dpi or higher. Text as small as 2 pt. is perfectly legible (with High Definition mode).																																																																																																															
<b>Print speed</b>	<table border="1"> <thead> <tr> <th rowspan="2">Print Modes</th> <th colspan="3">Arizona 13x0 XT</th> <th colspan="2">Flatbed</th> <th colspan="2">RMO</th> </tr> <tr> <th>1340 XT</th> <th>1360 XT</th> <th>1380 XT</th> <th>m<sup>2</sup>/h</th> <th>ft<sup>2</sup>/h</th> <th>m<sup>2</sup>/h</th> <th>ft<sup>2</sup>/h</th> </tr> </thead> <tbody> <tr> <td>High-Key</td> <td>•</td> <td>•</td> <td>•</td> <td>52.8</td> <td>568.3</td> <td>38.6</td> <td>415.5</td> </tr> <tr> <td>Express</td> <td>•</td> <td>•</td> <td>•</td> <td>35.3</td> <td>380.0</td> <td>25.8</td> <td>277.7</td> </tr> <tr> <td>Production-Fast</td> <td></td> <td></td> <td>•</td> <td>25.9</td> <td>278.8</td> <td>18.8</td> <td>202.4</td> </tr> <tr> <td>Production</td> <td>•</td> <td>•</td> <td>•</td> <td>21.3</td> <td>229.3</td> <td>17</td> <td>183.0</td> </tr> <tr> <td>Quality</td> <td>•</td> <td>•</td> <td>•</td> <td>15.0</td> <td>161.5</td> <td>12</td> <td>129.2</td> </tr> <tr> <td>Quality-Matte</td> <td>•</td> <td>•</td> <td>•</td> <td>10.8</td> <td>116.3</td> <td>7.9</td> <td>85.0</td> </tr> <tr> <td>Quality-Density</td> <td>•</td> <td>•</td> <td>•</td> <td>8.2</td> <td>88.3</td> <td>6.3</td> <td>67.8</td> </tr> <tr> <td>Quality-Layered (2)</td> <td></td> <td>•</td> <td>•</td> <td>7.5</td> <td>80.7</td> <td>6</td> <td>64.6</td> </tr> <tr> <td>Quality-Layered (3)</td> <td></td> <td>•</td> <td>•</td> <td>5.0</td> <td>53.8</td> <td>4</td> <td>43.1</td> </tr> <tr> <td>Fine Art</td> <td>•</td> <td>•</td> <td>•</td> <td>11.9</td> <td>128.1</td> <td>9.5</td> <td>102.3</td> </tr> <tr> <td>High Definition</td> <td>•</td> <td>•</td> <td>•</td> <td>6.4</td> <td>68.9</td> <td>6</td> <td>64.6</td> </tr> <tr> <td>Varnish (High Gloss)</td> <td></td> <td>•</td> <td>•</td> <td>-5</td> <td>53.8</td> <td>n.a.</td> <td>n.a</td> </tr> </tbody> </table>	Print Modes	Arizona 13x0 XT			Flatbed		RMO		1340 XT	1360 XT	1380 XT	m <sup>2</sup> /h	ft <sup>2</sup> /h	m <sup>2</sup> /h	ft <sup>2</sup> /h	High-Key	•	•	•	52.8	568.3	38.6	415.5	Express	•	•	•	35.3	380.0	25.8	277.7	Production-Fast			•	25.9	278.8	18.8	202.4	Production	•	•	•	21.3	229.3	17	183.0	Quality	•	•	•	15.0	161.5	12	129.2	Quality-Matte	•	•	•	10.8	116.3	7.9	85.0	Quality-Density	•	•	•	8.2	88.3	6.3	67.8	Quality-Layered (2)		•	•	7.5	80.7	6	64.6	Quality-Layered (3)		•	•	5.0	53.8	4	43.1	Fine Art	•	•	•	11.9	128.1	9.5	102.3	High Definition	•	•	•	6.4	68.9	6	64.6	Varnish (High Gloss)		•	•	-5	53.8	n.a.	n.a
Print Modes	Arizona 13x0 XT			Flatbed		RMO																																																																																																										
	1340 XT	1360 XT	1380 XT	m <sup>2</sup> /h	ft <sup>2</sup> /h	m <sup>2</sup> /h	ft <sup>2</sup> /h																																																																																																									
High-Key	•	•	•	52.8	568.3	38.6	415.5																																																																																																									
Express	•	•	•	35.3	380.0	25.8	277.7																																																																																																									
Production-Fast			•	25.9	278.8	18.8	202.4																																																																																																									
Production	•	•	•	21.3	229.3	17	183.0																																																																																																									
Quality	•	•	•	15.0	161.5	12	129.2																																																																																																									
Quality-Matte	•	•	•	10.8	116.3	7.9	85.0																																																																																																									
Quality-Density	•	•	•	8.2	88.3	6.3	67.8																																																																																																									
Quality-Layered (2)		•	•	7.5	80.7	6	64.6																																																																																																									
Quality-Layered (3)		•	•	5.0	53.8	4	43.1																																																																																																									
Fine Art	•	•	•	11.9	128.1	9.5	102.3																																																																																																									
High Definition	•	•	•	6.4	68.9	6	64.6																																																																																																									
Varnish (High Gloss)		•	•	-5	53.8	n.a.	n.a																																																																																																									
<b>Ink system</b>	IJC357 UV-curable inks packed in quick-change, 2 litre bags for: Black, Cyan, Magenta, Yellow, Light Cyan, Light Magenta. White and Varnish packed in 1 litre bags.																																																																																																															
<b>System architecture</b>	True flatbed for rigid media printing with available Roll Media Option for flexible media printing.																																																																																																															
<b>Geometric accuracy</b>	<table border="1"> <thead> <tr> <th rowspan="2"></th> <th colspan="2">Measured Over (mm)</th> <th colspan="2">Maximum Error (mm)</th> </tr> <tr> <th>Flatbed</th> <th>RMO</th> <th>Flatbed</th> <th>RMO</th> </tr> </thead> <tbody> <tr> <td>Line length (system width)</td> <td>2,500</td> <td>2,190</td> <td>± 0.8</td> <td>± 0.6</td> </tr> <tr> <td>Line length (system height)</td> <td>3,080</td> <td>2,000</td> <td>± 1.0</td> <td>± 1.5</td> </tr> <tr> <td>Line straightness (system width)</td> <td>2,500</td> <td>2,190</td> <td>0.7</td> <td>0.7</td> </tr> <tr> <td>Line straightness (system height)</td> <td>3,080</td> <td>2,000</td> <td>0.7</td> <td>2.0</td> </tr> <tr> <td>Diagonal Error ("square-ness")</td> <td>3,080x2,500</td> <td>2,000x2,190</td> <td>1.0</td> <td>2.5</td> </tr> </tbody> </table>		Measured Over (mm)		Maximum Error (mm)		Flatbed	RMO	Flatbed	RMO	Line length (system width)	2,500	2,190	± 0.8	± 0.6	Line length (system height)	3,080	2,000	± 1.0	± 1.5	Line straightness (system width)	2,500	2,190	0.7	0.7	Line straightness (system height)	3,080	2,000	0.7	2.0	Diagonal Error ("square-ness")	3,080x2,500	2,000x2,190	1.0	2.5																																																																													
	Measured Over (mm)		Maximum Error (mm)																																																																																																													
	Flatbed	RMO	Flatbed	RMO																																																																																																												
Line length (system width)	2,500	2,190	± 0.8	± 0.6																																																																																																												
Line length (system height)	3,080	2,000	± 1.0	± 1.5																																																																																																												
Line straightness (system width)	2,500	2,190	0.7	0.7																																																																																																												
Line straightness (system height)	3,080	2,000	0.7	2.0																																																																																																												
Diagonal Error ("square-ness")	3,080x2,500	2,000x2,190	1.0	2.5																																																																																																												
<b>Rigid media</b>	Maximum Area: 308 x 250 cm / 121.3 x 98.4 inches (320 x N cm permitted w/308 cm vacuum) Maximum Thickness: 50.8 mm / 2.0 inches Maximum Mass: 34 kg/m <sup>2</sup> / 7 lbs/ft <sup>2</sup>																																																																																																															
<b>Rigid media print area</b>	Up to: 309 x 251 cm / 121.7 x 98.8 inches (321 x N cm permitted w/308 cm vacuum)																																																																																																															
<b>Media roll specification</b>	90 to 220 cm / 35.4 to 86.6 inches. Up to 50 kg / 110 lbs (at any width). Maximum diameter: 240 mm (9.45 inches). Core: 3 inches (inside). Bias: Print-side-in or print-side-out. Most types (application dependent)																																																																																																															
<b>Roll media print width</b>	Up to 219 cm / 86.2 inches																																																																																																															
<b>Image processing</b>	ONYX Thrive 18 (421 configuration or greater recommended)																																																																																																															
<b>Connectivity</b>	10/100/1000 Base-T																																																																																																															
<b>Arizona Xpert</b>	Arizona Xpert offers a unique tool set to save time and money in the creation of complex, multi-layered and duplex applications. The "Arizona Xpert Resale license" and the "Add Arizona Xpert Permission" are included with every Arizona 1300 printer and require ONYX Thrive to be installed.																																																																																																															
<b>Electrical power / Compressed air</b>	2 x 200-240 VAC, 50/60 Hz, Single-phase, 16A per circuit Circuit Breakers: North America: 20A. Europe: 16A. ROW: See CB Scheme Report Clean, dry, compressed air using a Coalescing Filter. Pressure Regulator set to 690 kPa (100 psi) and connects air regulator to 0.5 inch or 12mm OD air tubing. Peak flow: 57 l/min at 690 kPa (2 cfm at 100 psi)																																																																																																															
<b>Environment</b>	Temperature: 18° to 30°C (64° to 86°F) Relative humidity: 30 to 70% (non-condensing) Ventilation: 1,200 m <sup>3</sup> per hour / 700 cfm minimum (see Site Preparation Guide) Altitude: 2,750 m (9,020 feet) maximum, however some components specify a limit of 2,000 m (6,560 feet)																																																																																																															
<b>Size/Weight</b>	Printer only: 4.66 m x 3.83 m (183.5" x 150.8"), 1,660 kg (3,660 lbs.) Printer + Roll Media Option: 4.66 m x 4.12 m (183.5" x 162.2"), 1,910 kg (4,211 lbs.) Table height: 0.88 m (34.6") / Overall height: 1.3 m (51.2")																																																																																																															

**Canon Inc.**  
canon.com

**Canon Europe**  
canon-europe.com

English Edition  
© Canon Europa N.V., 2019

© 2019 Illustrations and specifications do not necessarily apply to products and services offered in each local market. Technical specifications are subject to change without prior notice.

All other trademarks are the property of their respective owners.

